

# ATEX LED LINE



Industrial LED light fitting, suitable for operation in hazardous areas.  
 High degree of protection IP66/68.  
 Aluminum enclosure with mounting slots.  
 Epoxy resin diffuser.  
 Color temperature 4000K.  
 Cable not replaceable (cable options 5 and 10 m).  
 Other measures on request.

Can be used:  
 Zone 2 and 22.

## Selection table:

Description:	Lenght A:	Cable lenght:	Power:	Luminous flux:	Article No.:
ATEX LED LINE 205	200 mm	5 m	1 W	77 lm	1A4801
ATEX LED LINE 210	200 mm	10 m	1 W	77 lm	1A4802
ATEX LED LINE 305	300 mm	5 m	2 W	152 lm	1A4803
ATEX LED LINE 310	300 mm	10 m	2 W	152 lm	1A4804
ATEX LED LINE 405	400 mm	5 m	3 W	220 lm	1A4805
ATEX LED LINE 410	400 mm	10 m	3 W	220 lm	1A4806
ATEX LED LINE 505	500 mm	5 m	4 W	311 lm	1A4807
ATEX LED LINE 510	500 mm	10 m	4 W	311 lm	1A4808
ATEX LED LINE 605	600 mm	5 m	5 W	385 lm	1A4809
ATEX LED LINE 610	600 mm	10 m	5 W	385 lm	1A4810
ATEX LED LINE 705	700 mm	5 m	6 W	458 lm	1A4811
ATEX LED LINE 710	700 mm	10 m	6 W	458 lm	1A4812
ATEX LED LINE 805	800 mm	5 m	7 W	523 lm	1A4813
ATEX LED LINE 810	800 mm	10 m	7 W	523 lm	1A4814
ATEX LED LINE 905	900 mm	5 m	8 W	623 lm	1A4815
ATEX LED LINE 910	900 mm	10 m	8 W	623 lm	1A4816
ATEX LED LINE 1005	1000 mm	5 m	9 W	675 lm	1A4817
ATEX LED LINE 1010	1000 mm	10 m	9 W	675 lm	1A4818
ATEX LED LINE 1105	1100 mm	5 m	10 W	770 lm	1A4819
ATEX LED LINE 1110	1100 mm	10 m	10 W	770 lm	1A4820
ATEX LED LINE 1205	1200 mm	5 m	11 W	825 lm	1A4821
ATEX LED LINE 1210	1200 mm	10 m	11 W	825 lm	1A4822
ATEX LED LINE 1305	1300 mm	5 m	12 W	899 lm	1A4823
ATEX LED LINE 1310	1300 mm	10 m	12 W	899 lm	1A4824

Colors: Red | Green | Blue (on request) | Configuration: Luminaires connected in series (on request) | Other options on request

## Technical data:

Marking:	
Certificate:	LOM 13 ATEX 4081 X
Application:	Industrial
Housing:	Aluminum, RAL 9010
LED:	5000h L80B10   8000h L55B10   13000h L37B10   23000h L12B10
Diffuser:	Epoxy resin
Temperatura de operación:	-20°C to +45°C
Rated voltage:	24V DC
Ingress protection:	IP66/68   IK08
Energy efficiency class:	F
Cable entries:	Non-replaceable cable. Other cable configurations on request.

